

FORESTECH - Data Sheet



Description

FORESTECH is a BKT bias steel-belted tire, suitable for forestry applications with forwarders. It provides excellent traction even in heavy-duty service. The strong bead and shoulder area ensure high puncture resistance as well as a longer tire life-cycle. As a result, you can deal with the most difficult operating conditions in a forest without concern.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Forwarder

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
710/40 - 22.5	STEEL BELTED	94059683	LS2	161 A8/ 165 A2	20	AG 24.00		28	45.9	21.7	142.2	TL	E11-106R-005273
600/55 - 26.5	STEEL BELTED	94031238	LS2	165 A8/172 A2	20	AG 20.00		24	52.6	24.3	158.7	TL	E11-106R-003419
710/45 - 26.5	STEEL BELTED	94029754	LS2	168 A8/175 A2	20	AG 24.00		28	52.8	24.4	159.3	TL	E11-106R-003420
750/55 - 26.5	STEEL BELTED	94031719	LS2	177 A8/184 A2	20	AG 24.00		29.7	58.5	26.8	175.9	TL	E11-106R-003347

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 04:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..