

FORESTMAX - Technical Specifications



Description

FORESTMAX is BKT's new radial tire for tractors, which has been mainly developed for forestry applications, but can also be employed for some specific farming operations such as soil milling and stone breaking.

Its multi-ply polyester casing and the reinforced sidewall are designed to withstand the harsh forestry operating conditions. In addition, the cut-and-chip-resistant tread compound and the steel-belted structure significantly minimize the risk of punctures in the woodland. The tire features a robust open shoulder providing best traction and top stability even on rugged and uneven terrains. The combination of tread resistance and the particular shoulder design stand for optimum self-cleaning properties along with a long tire life making FORESTMAX your ideal partner in the forest.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STEEL BELTED
Type	TL
Tyre Size	650/65R38
LI/SS	164A8/160B

Dimensions US Standard

Usa code	94074044
Section Width (inch)	25.4
Overall Diameter (inch)	71.3
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	215.2
Rim Rec	DW 20 B
Rim Alt	DW21B; DW23B
ECE	E11-106R-008829

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35
30	6750	7540	7740	8530	9230	9520	9920
25	7500	8380	8600	9480	10250	10580	11020
20	8020	8970	9200	10140	10970	11330	11790
15	8320	9300	9550	10530	11380	11750	12230
12	9230	10310	10570	11660	12600	13020	13560
10	10050	11230	11520	12700	13730	14190	14770
5	11240	12570	12900	14220	15370	15870	16530
5 forestry service	-	-	-	-	-	-	13560
0 forestry service	-	-	-	-	-	-	25350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 11:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..