

FS 216 - Technical Specifications



Description

FS 216 has a robust log design with optimum angle and wider width to enhance traction performance for loggers and skidders. It provides excellent cut and chip resistance under the most critical operating conditions and ensures maximum protection against possible damages at any time.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Log Skidder

Version	STEEL BELTED
Type	TT
Tyre Size	18.4 - 30

Dimensions International Standard

Ply Rating	10
Section Width (mm)	467
Overall Diameter (mm)	1577
Static Loaded Radius (mm)	724
Rolling Circumference (mm)	4736
Rim Rec	DW 16 A
ECE	E11-106R-003638
TRA Code	LS2

Load capacity (Kg)

km/h / bar	2.10	1.70
10	3820	-
30	-	2725

Printed on 30/11/2023 01:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..