

FS 216 - Technical Specifications



Description

FS 216 has a robust log design with optimum angle and wider width to enhance traction performance for loggers and skidders. It provides excellent cut and chip resistance under the most critical operating conditions and ensures maximum protection against possible damages at any time.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Log Skidder

Version	STEEL BELTED
Type	TT
Tyre Size	23.1 - 26

Dimensions International Standard

Ply Rating	14
Section Width (mm)	587
Overall Diameter (mm)	1615
Static Loaded Radius (mm)	726
Rolling Circumference (mm)	4780
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003411
TRA Code	LS2

Load capacity (Kg)

km/h / bar	2.40	2.10
10	5760	-
30	-	4125

Printed on 24/04/2024 17:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..