

## GF 305 FARM TRAILER - Technical Specifications



### Description

GF 305 FARM TRAILER has been designed for implements in transport operations. This tire is naturally gentle on the ground and protects the field against damage.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery

Version	STANDARD
Type	TL
Tyre Size	205/65 - 10 (20.5 x 8.00 - 10)

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	212
Overall Diameter (mm)	520
Static Loaded Radius (mm)	223
Rolling Circumference (mm)	1508
Rim Rec	6.00
ECE	E11-106R-003578

## Load capacity (Kg)

km/h / bar	6.20
40	695

Printed on 24/04/2024 16:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..