GF 305 FARM TRAILER - Technical Specifications

Description

GF 305 FARM TRAILER has been designed for implements in transport operations. This tire is naturally gentle on the ground and protects the field against damage.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery

Version	STANDARD
Type	TL
Tyre Size	205/65 - 10 (20.5 x 8.00 - 10)

Dimensions US Standard

Usa code	94041237
Ply Rating	10
Section Width (inch)	8.3
Overall Diameter (inch)	20.5
Static Loaded Radius (inch)	8.8
Rolling Circumference (inch)	59.4
Rim Rec	6.00
ECE	E11-106R-003578

Load capacity (lbs)

mph / psi	90
25	1530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 10:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..