



GR 288 - Data Sheet



Description

GR 288 (G-2/L-2) is a versatile bias-ply tire for graders or loaders. It is ideal for use in construction, site preparation, road building, and other soft or muddy environments. The self-cleaning tread pattern provides excellent traction, and you can expect a long tire life as a result of the special cut-and-chip-resistant compound.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Dozer • Loader

OTR: Grader

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
15.5 - 25	STANDARD	G2/L2	12	12.00/1.3	12.00/1.3 (DC)	385	1270	572	3772	TL	E11-106R-003606
17.5 - 25	DUAL BEAD HD	G2/L2	20	14.00/1.5	14.00/1.3 (DC)	445	1330	596	3950	TT	E11-106R-005407
17.5 - 25	STANDARD	G2/L2	12	14.00/1.5	14.00/1.5 (DC) ; 14.00/1.3 (DC)	445	1330	596	3950	TL	E11-106R-005339
17.5 - 25	STANDARD	G2/L2	16	14.00/1.5	14.00/1.3 (DC)	445	1330	596	3950	TL	E11-106R-004561
20.5 - 25	STANDARD	G2/L2	16	17.00/2.0	17.00/1.7	520	1480	656	4396	TL	E11-106R-005405
20.5 - 25	STANDARD	G2/L2	20	17.00/2.0	17.00/1.7	520	1480	656	4396	TL	E11-106R-005180
23.5 - 25	STANDARD	G2/L2	16	19.50/2.5		595	1610	708	4782	TL	E11-106R-005406
23.5 - 25	STANDARD	G2/L2	20	19.50/2.5		595	1610	708	4782	TL	E11-106R-005181

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/10/2024 09:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..