# JUMBO TRAX HD - Technical Specifications

## Description

JUMBO TRAX HD is a block pattern tire for skid steers. It features cut and chip resistance and is particularly suitable for heavy-duty service. The deep tread along with excellent sidewall protection provides an extended tire life-cycle. JUMBO TRAX HD is also available in a “special” version.

## UM

International Standard

## Construction

BIAS

## Machinery

Industrial: Skid Steer

| | |
|---|---|
| **Version** | SPECIAL |
| **Type** | TL |
| **Tyre Size** | 10 - 16.5 |

## Dimensions International Standard

| | |
|---|---|
| **Ply Rating** | 10 |
| **Section Width (mm)** | 268 |
| **Overall Diameter (mm)** | 795 |
| **Static Loaded Radius (mm)** | 363 |
| **Rolling Circumference (mm)** | 2345 |
| **Rim Rec** | 8.25 |

## Load capacity (Kg)

| km/h / bar | 5.20 |
|---|---|
| **10** | 2135 |
| **15** | 1685 |
| **25** | 1560 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 05:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..