



LG 307 - Data Sheet

Description

LG 307 is a lawn and garden tire suitable for mowers. The specific tread pattern makes the tire gentle on the ground to prevent turf damages, easing handling at the same time.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Mower



SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
20 X 10.00 - 8	STANDARD	94012831	4	8.00 I - 55; I - 70; I - 90	7.00 I - 55; I - 70; I - 90	10	19.5	8.5	56.5	TL	E11-106R-005200
20 X 10.00 - 8	STANDARD	94012848	6	8.00 I - 55; I - 70; I - 90	7.00 I - 55; I - 70; I - 90	10	19.5	8.5	56.5	TL	E11-106R-003462
20 X 12.00 - 10	STANDARD	94012855	4	8.5 I - 55; I - 70; I - 90		11.2	19.7	8.7	56.5	TL	E11-106R-003463

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 11:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..