

## LG 408 - Technical Specifications



### Description

LG 408 is a lawn and garden tire suitable for mowers and small tractors. The specific tread pattern makes the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG 408 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Mower • Small Tractor

Version	STANDARD
Type	TL
Tyre Size	26.5 X 14.00 - 12

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	380
Overall Diameter (mm)	665
Static Loaded Radius (mm)	293
Rolling Circumference (mm)	1929
Rim Rec	12.00 l
ECE	E11-106R-004650

## Load capacity (Kg)

km/h / bar	3.40
15	1750

Printed on 19/04/2024 18:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..