



LG 408 - Data Sheet



Description

LG 408 is a lawn and garden tire suitable for mowers and small tractors. The specific tread pattern makes the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG 408 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Mower • Small Tractor

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
24 X 13.00 - 12	ARAMID BELTED	94012909	6	10.5 I - 55 ; I - 70 ; I - 90		12.8	24	10.6	69.1	TL	E11-106R-003364
24 X 13.00 - 12	STANDARD	94012862	4	10.5 I - 55 ; I - 70 ; I - 90		12.8	24	10.6	69.1	TL	E11-106R-005204
24 X 13.00 - 12	STANDARD	94012879	6	10.5 I - 55 ; I - 70 ; I - 90		12.8	24	10.6	69.1	TL	E11-106R-003464
26.5 X 14.00 - 12	ARAMID BELTED	94012916	6	12.00 I		15	26.2	11.5	75.9	TL	E11-106R-005223
26.5 X 14.00 - 12	STANDARD	94012886	4	12.00 I		15	26.2	11.5	75.9	TL	E11-106R-005205
26.5 X 14.00 - 12	STANDARD	94012893	6	12.00 I		15	26.2	11.5	75.9	TL	E11-106R-003353
26.5 X 14.00 - 12	STANDARD	94048717	10	12.00 I		15	26.2	11.5	75.9	TL	E11-106R-004650

Printed on 19/04/2024 16:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..