

LIFTMAX LM 63 - Technical Specifications



Description

LIFTMAX LM 63 has been specially developed for industrial and logistics operations. The 3-rib tread design provides low rolling resistance with good wet grip and uniform tread wear with better handling. It is an All Steel radial tire with multilayer steel belts offering lower vibration as well as enhanced stability and comfort

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Hay Harvester

Industrial: Tow Tractor • Trailer

Version	STANDARD
Type	TL
Tyre Size	7.00 R 12
LI/SS	136 A5

Dimensions US Standard

Usa code	94066209
Overall Width (inch)	7.7
Overall Diameter (inch)	26.6
Rim Rec	5.00S

Load capacity (lbs)

mph / psi	145
15	4940

Printed on 20/05/2024 02:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..