

LOADER PLUS - Technical Specifications

Description

LOADER PLUS (L-3) is a bias-ply tire specially designed for loaders. The tread compound provides cut-and-chip-resistant properties and suites best for loading and dozing operations.



UM

International Standard

Construction

 BIAS

Machinery

Industrial: Dozer • Loader

OTR: Dozer • Loader

Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

Dimensions International Standard

Ply Rating	24
Overall Width (mm)	610
Overall Diameter (mm)	1640
Static Loaded Radius (mm)	749
Rolling Circumference (mm)	4855
Rim Rec	19.50/2.5
TRA Code	L3
Tread Depth	32

Load capacity (Kg)

km/h / bar	4.75
10	12500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/03/2025 11:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..