

## MAGLIFT ECO - Technical Specifications



### Description

MAGLIFT ECO has been particularly designed for forklifts. The tire features a wide lug pattern providing maximum stability and optimized load distribution. Its reinforced structure eliminates slippage risks whilst the specifically designed rim guard ensures protection against wheel damage. MAGLIFT ECO shows excellent traction as well as low rolling resistance and low heat built up for improved efficiency.

### UM

US Standard

### Construction

◆ SOLID

### Machinery

Industrial: Forklift

Version	LIP
Type	
Tyre Size	21 X 8 - 9 (200 / 75 - 9)

## Dimensions US Standard

Usa code	94065639
Section Width (inch)	6.9
Overall Diameter (inch)	20.5
Rim Rec	6.00 E - 9

## Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	6075
15 STEER WHEEL	4675

Printed on 24/04/2024 17:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..