

MH TR 182 - Data Sheet



Description

MH TR 182 is suitable for transport operations with mobile home vehicles. It is a road-oriented, high-speed tire that significantly reduces fuel consumption. MH TR 182 ensures long durability and high performance along the entire product life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Mobile Home

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
8 - 14.5	STANDARD	94008605	14	6.00 MH		8.1	28	TL
8 - 14.5	STANDARD	94008575	8	6.00 MH		8.1	28	TL
8 - 14.5	STANDARD	94008582	10	6.00 MH		8.1	28	TL
8 - 14.5	STANDARD	94008599	12	6.00 MH		8.1	28	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 23:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..