



## MP 567 - Data Sheet



### Description

MP 567 is an agro-industrial tire suitable for field and road transport and municipality/maintenance operations. It is the perfect tire for telehandlers and implement machinery. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties. This tire ensures a comfortable driving experience, together with a longer service life.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Telehandler  
Industrial: Telehandler • Universal Vehicle

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TKPH	ECE
11.5/80 - 15	IMPLEMENT		123 A8	135 A8	12	8 LB		290	875	0	0	TL		E11-106R-004621
10.0/75 - 15.3	IMPLEMENT		123 A8	135 A8	18	9.0		258	774	365	2401	TL	1	E11-106R-003607
10.0/75 - 15.3	IMPLEMENT		111 A8	123 A8	10	9.0		258	774	365	2401	TL	1	E11-106R-003526
10.0/75 - 15.3	IMPLEMENT		114 A8	126 A8	12	9.0		258	774	365	2401	TL	1	E11-106R-003527
10.0/75 - 15.3	IMPLEMENT		118 A8	130 A8	14	9.0		258	774	365	2401	TL	1	E11-106R-003528
11.5/80 - 15.3	IMPLEMENT		119 A8	131 A8	10	9.0		292	868	393	2578	TL	1	E11-106R-003529
11.5/80 - 15.3	IMPLEMENT		126 A8	139 A8	14	9.0		292	868	393	2578	TL	1	E11-106R-003373
11.5/80 - 15.3	IMPLEMENT		130 A8	143 A8	18	9.0		292	868	393	2578	TL	1	E11-106R-003392
10.5 - 18	SPECIAL				12	9	9 SDC	273	905	415	2768	TL		
10.5 - 18	STANDARD				10	9	9 SDC	273	905	415	2768	TT		E4-54R-0022624
10.5 - 18	STANDARD				10	9	9 SDC	273	905	415	2768	TL		E4-54R-0022624
10.5 - 18	STANDARD				12	9	9 SDC	273	905	415	2768	TL		E4-54R-0022625
12.0/75 - 18 (300/75 - 18)	IMPLEMENT		126 A8	139 A8	12	W 9	9 ; 11	298	915	426	2723	TL		E11-106R-006701
12.5 - 18	STANDARD				10	11	12 SDC	325	990	450	2940	TT		E4-54R-0022626
12.5 - 18	STANDARD				10	11	12 SDC	325	990	450	2940	TL		E4-54R-0022626
12.5 - 18	STANDARD				12	11	12 SDC	325	990	450	2940	TT		E4-54R-0022627
12.5 - 18	STANDARD				12	11	12 SDC	325	990	466	3024	TL		E4-54R-0022627
12.5 - 18	STANDARD				16	11	12 SDC	325	990	450	2940	TL		E4-54R-0022628
18 - 19.5 IND	STANDARD	165 B / 167 A8			18	14.00		460	1104	498	3280	TL	1	E11-106R-003663
18 - 19.5 IND	STANDARD	160 B / 162 A8			16	14.00		460	1104	498	3280	TL	1	E11-106R-003639
10.5 - 20	STANDARD				10	9	9 SDC	270	955	445	2880	TT		E4-54R-0022630
10.5 - 20	STANDARD				10	9	9 SDC	270	955	445	2880	TL		E4-54R-0022630
12.5 - 20	HD				12	11.0	12 SDC	325	1040	490	3142	TL		
12.5 - 20	STANDARD				16	11.0	12 SDC	325	1040	490	3142	TL		
12.5 - 20	STANDARD				10	11.0	12 SDC	325	1040	490	3142	TT		E4-54R-0022632
12.5 - 20	STANDARD				10	11.0	12 SDC	325	1040	490	3142	TL		E4-54R-0022632

12.5 - 20	STANDARD	12	11.0	12 SDC	325	1040	490	3142	TT	E4-54R-0022633
12.5 - 20	STANDARD	12	11.0	12 SDC	325	1040	490	3142	TL	E4-54R-0022633
14.5 - 20	HD	14	11	12 SDC	360	1116	495	3315	TL	
14.5 - 20	STANDARD	10	11	12 SDC	360	1116	495	3315	TL	E4-54R-0022636
14.5 - 20	STANDARD	12	11	12 SDC	360	1116	495	3315	TL	E4-54R-0022637
14.5 - 20	STANDARD	14	11	12 SDC	360	1116	495	3315	TL	E4-54R-0022638
14.5 - 20	STANDARD	16	11	12 SDC	360	1116	495	3315	TL	
14.5 - 20	STANDARD	18	11	12 SDC	360	1116	495	3315	TL	E11-54R-0017876
16.0/70 - 20 (405/70 - 20)	STANDARD	14	13 SDC	12	405	1128	490	3350	TT	E4-54R-0022639
16.0/70 - 20 (405/70 - 20)	STANDARD	14	13 SDC	12	405	1128	490	3350	TL	E4-54R-0022639

Printed on 25/04/2024 06:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..