

MP 570 - Technical Specifications



Description

MP 570 is an agro-industrial tire, which is suitable for excavators and backhoe loaders. This tire provides good traction and durability, as well as excellent self-cleaning properties in all operating conditions.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Backhoe Loader

Industrial: Backhoe Loader • Excavator • Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	14.5 - 20

Dimensions International Standard

Ply Rating	12
Section Width (mm)	360
Overall Diameter (mm)	1116
Static Loaded Radius (mm)	505
Rolling Circumference (mm)	3325
Rim Rec	11
Rim Alt	12 SDC
ECE	E11-106R-005342

Load capacity (Kg)

km/h / bar	3.00
65	2430
50	2500

Printed on 13/04/2024 01:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..