

## MT 612 - Technical Specifications



### Description

MT 612 has been specially designed for multipurpose use on and off the road. Its strong casing allows carrying heavy loads at high speed whereas its broad lugs provide outstanding traction. The extra tread width ensures excellent flotation on sand and mud.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

Industrial: Universal Vehicle

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

## Dimensions International Standard

Ply Rating	20
Section Width (mm)	390
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	594
Rolling Circumference (mm)	3827
Rim Rec	10
ECE	E11-54R-0021125

## Load capacity (Kg)

km/h / bar	7.60
80 LS	4875
80 LD	4375

Printed on 30/04/2024 06:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..