

MT 612 - Technical Specifications



Description

MT 612 has been specially designed for multipurpose use on and off the road. Its strong casing allows carrying heavy loads at high speed whereas its broad lugs provide outstanding traction. The extra tread width ensures excellent flotation on sand and mud.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Industrial: Universal Vehicle

| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 16.0/70 - 20 |

Dimensions International Standard

| | |
|-----------------------------------|---------|
| Ply Rating | 16 |
| Section Width (mm) | 405 |
| Overall Diameter (mm) | 1095 |
| Static Loaded Radius (mm) | 520 |
| Rolling Circumference (mm) | 3327 |
| Rim Rec | 13.00 T |

Load capacity (Kg)

| | |
|-------------------|-------------|
| km/h / bar | 4.50 |
| 80 LS | 3075 |
| 80 LD | 2725 |

Printed on 18/04/2024 00:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..