

MULTI RIB - Technical Specifications



Description

MULTI RIB is an agro-industrial tire for soil tillage and transport applications with 2WD tractors and implement machinery. It offers excellent handling throughout its long product life-cycle. Several versions are available for every need: an "aramid belted" version with improved puncture resistance, while the "HD" is made of a special cut-and-chip resistance compound.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: 2WD Tractor • Implement Machinery

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 11.00 - 16 |

Dimensions US Standard

| | |
|-------------------------|-----------------|
| Usa code | 94006199 |
| Ply Rating | 12 |
| Section Width (inch) | 12.4 |
| Overall Diameter (inch) | 36.6 |
| Rim Rec | W10 L |
| Rim Alt | W 8 ; W 8 L |
| ECE | E11-106R-004649 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 60 |
| 25 | 3420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 06/05/2025 02:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..