

## MULTI RIB - Technical Specifications



### Description

MULTI RIB is an agro-industrial tire for soil tillage and transport applications with 2WD tractors and implement machinery. It offers excellent handling throughout its long product life-cycle. Several versions are available for every need: an "aramid belted" version with improved puncture resistance, while the "HD" is made of a special cut-and-chip resistance compound.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: 2WD Tractor • Implement Machinery

Version	HD
Type	TL
Tyre Size	11.00 - 16

## Dimensions US Standard

Usa code	94061624
Ply Rating	12
Section Width (inch)	12.4
Overall Diameter (inch)	36.6
Rim Rec	W10 L
Rim Alt	W 8 ; W 8 L

## Load capacity (lbs)

mph / psi	60
25	3420

Printed on 02/05/2024 16:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..