

# MULTIMAX MP 513 - Technical Specifications



## Description

MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Universal Vehicle • Fertilizer Truck  
Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	285/80 R 16 MPT
LI/SS	128 G

# Dimensions International Standard

Section Width (mm)	304
Overall Diameter (mm)	866
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2617
Rim Rec	W 10
ECE	E11-54R-0020958

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	4.0
90	840	985	1180	1360	1540	1800
65	905	1065	1270	1465	1660	1945
40	965	1135	1355	1560	1770	2070

Printed on 03/05/2024 10:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..