

# MULTIMAX MP 513 - Technical Specifications



## Description

MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Universal Vehicle • Fertilizer Truck  
Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	136 G

Dimensions US Standard

Usa code	94038428
Section Width (inch)	16
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	128.1
Rim Rec	13
Rim Alt	13 SDC ; 12 SDC
ECE	E4-54R-0022640

Load capacity (lbs)

mph / psi	23	29	36	44	51
55	2950	3480	4010	4500	4940
40	3210	3780	4350	4880	5370
25	3410	4010	4620	5180	5690

Printed on 03/05/2024 10:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..