

# MULTIMAX MP 513 - Technical Specifications



## Description

MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Universal Vehicle • Fertilizer Truck  
Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	425/55 R 17 MPT
LI/SS	142 A8/B

Dimensions US Standard

Usa code	94065110
Section Width (inch)	16.6
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	15.7
Rolling Circumference (inch)	106.5
Rim Rec	13
Rim Alt	13.00
ECE	E11-106R-006433

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	51	58
30	2280	2810	3340	3800	4330	4850	5380	5840
25	2280	2810	3340	3800	4330	4850	5380	5840
20	2450	3010	3570	4080	4640	5200	5580	6260
15	2540	3120	3700	4220	4810	5390	5790	6490

Printed on 03/05/2024 16:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..