

# MULTIMAX MP 515 - Technical Specifications



## Description

MULTIMAX MP 515 is an agro-industrial radial tire designed for universal vehicles and fertilizer trucks. It is suitable for municipality and transport applications. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties and great traction. The strong steel-belted nylon casing and the reinforced shoulder ensure extraordinary durability. MULTIMAX MP 515 is the perfect tire also at high speeds (90km/h).

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Universal Vehicle • Fertilizer Truck

Version	STANDARD
Type	TL
Tyre Size	425/75 R 20 MPT
LI/SS	148 G

## Dimensions International Standard

Section Width (mm)	421
Overall Diameter (mm)	1146
Static Loaded Radius (mm)	522
Rolling Circumference (mm)	3491
Rim Rec	13
Rim Alt	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12
ECE	E11-54R-0017872

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	4.0
90	1540	1810	2150	2490	2820	3150
65	1675	1965	2335	2705	3060	3420
40	1775	2085	2475	2865	3245	3625

Printed on 26/04/2024 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..