

## MULTIMAX MP 525 - Data Sheet



### Description

MULTIMAX MP 525 is an All-Steel multi-purpose radial tire designed for universal vehicle, telehandlers, compact loaders, and graders in agro-industrial applications.. The tire has been specifically developed to carry heavy loads at higher speeds both on and off the road. Indeed, the large non-directional tread design provides exceptional traction on any surface in addition to excellent self-cleaning properties. The strong sidewall ensures exceptional lateral stability in lift mode, making it the ideal choice for agricultural and material handling operations. MULTIMAX MP 525 is made of a unique, cut- and-chip-resistant tread compound that stands for a longer tire service life thanks to its extraordinary resistance against any kinds of cuts and punctures.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Compact Loader • Grader • Telehandler

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
<b>405/70 R 18</b> <b>(15.5/70 R 18)</b>	STANDARD	146 J/141 B/153 A2	13	11; 12	405	1025	462	3122	TL	E11-54R-0022030
<b>405/70 R 20</b> <b>(16.0/70 R 20)</b>	STANDARD	152 J/168 A2	13	12; 13 SDC	405	1076	482	3260	TL	E11-54R-0020576
<b>455/70 R 24</b>	STANDARD	154 G/154 B/165 A2	14	13; DW14L	455	1250	571	3794	TL	E11-54R-0021226

Printed on 29/04/2024 12:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..