

MULTIMAX MP 527 - Technical Specifications



Description

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing and a long service life.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	440/80 R 28 IND
LI/SS	156 A8/B

Dimensions US Standard

Usa code	94052714
Section Width (inch)	17.4
Overall Diameter (inch)	55.7
Static Loaded Radius (inch)	25.5
Rolling Circumference (inch)	168.1
Rim Rec	DW 14 L
Rim Alt	DW 13 ; DW 13 L ; DW 15 L
ECE	E11-106R-002984

Load capacity (lbs)

mph / psi	23	29	32	35	38	41	44	46	49	52
30	5070	6010	6480	6940	7410	7880	8360	8820	-	-
25	5070	6010	6480	6940	7410	7880	8360	8820	-	-
20	5470	6460	6960	7450	7950	8440	8940	9440	-	-
15	5670	6700	7210	7730	8240	8750	9270	9790	-	-
5 Cyc.	6260	7650	8360	9050	9740	10440	11130	11840	12530	13230
Static	9610	11750	12810	13880	14950	16020	17080	18140	19210	20280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 14:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..