

PL 801 - Technical Specifications



Description

PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Hay Harvester • Rotor Rake / Tedder • Forklift
Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions US Standard

Usa code	94007127
Ply Rating	10
Section Width (inch)	6.2
Overall Diameter (inch)	21.4
Rim Rec	4.00 E
ECE	E11-106R-003564

Load capacity (lbs)

mph / psi	123
15 LOAD WHEEL	3780
15 STEER WHEEL	2910
5 OTHER VEHICLES	3780
15 OTHER VEHICLES	2910
STATIC SIDE LOADER	4400

Printed on 05/05/2024 08:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..