



## PL 801 - Data Sheet



### Description

PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Hay Harvester • Rotor Rake / Tedder • Forklift  
Industrial: Forklift

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
<b>23 X 5</b> <b>(23 X 5 (- 13 ))</b>	STANDARD	94007028		6	3.75 P		6.1	25.2	TT	
<b>18 X 7 - 8</b> <b>(180/70 - 8)</b>	STANDARD	94006953		14	4.33 R	5.00 F	6.8	18.5	TT	
<b>18 X 7 - 8</b> <b>(180/70 - 8)</b>	STANDARD	94006977	121 A8	16	4.33 R	5.00 F	6.8	18.5	TT	E11-106R-003642
<b>5.00 - 8</b>	STANDARD	94007103		8	3.00 D	3.25 I	5.3	18.4	TT	E11-106R-003381
<b>5.00 - 8</b>	STANDARD	94032259		10	3.00 D	3.25 I	5.3	18.4	TT	
<b>21 X 8 - 9</b> <b>(200/75 - 9)</b>	STANDARD	94027842		16	6.00 E	7.00 E	7.9	21.1	TT	
<b>21 X 8 - 9</b> <b>(200/75 - 9)</b>	STANDARD	94006991		14	6.00 E	7.00 E	7.9	21.1	TT	E11-106R-003643
<b>6.00 - 9</b>	SPECIAL	94035052		10	4.00 E		6.2	21.4	TT	
<b>6.00 - 9</b>	STANDARD	94007127		10	4.00 E		6.2	21.4	TT	E11-106R-003564
<b>6.00 - 9</b>	STANDARD	94007158		12	4.00 E		6.2	21.4	TT	E11-106R-003565
<b>6.50 - 10</b>	STANDARD	94007165		10	5.00 F	5.50 F	7.3	23.4	TT	E11-106R-003566
<b>7.00 - 12</b>	STANDARD	94007196		12	5.00 S		7.4	27.2	TT	E11-106R-003567
<b>7.00 - 12</b>	STANDARD	94007219		14	5.00 S		7.4	27.2	TT	E11-106R-003398
<b>250 - 15</b> <b>(250/70 - 15)</b>	STANDARD	94007059		16	7.50 BD	7.0 ; 7.5	9.3	29.3	TT	
<b>250 - 15</b> <b>(250/70 - 15)</b>	STANDARD	94007066		20	7.50 BD	7.0 ; 7.5	9.3	29.3	TT	
<b>300 - 15</b> <b>(315/70 - 15)</b>	STANDARD	94007080		18	8.00 BD	8.0	11.6	33.1	TT	E11-106R-007161
<b>5.50 - 15</b>	STANDARD	94030545		8	4.50 E DT	4.50 E SDC	6.2	26.4	TT	
<b>7.00 - 15</b> <b>(30 X 8 - 15)</b>	STANDARD	94007363		14	6.0	5.50 BD ; 5.5	8.1	30.5	TT	
<b>7.00 - 15</b> <b>(29 X 8 - 15)</b>	STANDARD	94007233		12	5.5	4.33 R ; 5.0	7.9	29.5	TT	
<b>7.00 - 15</b> <b>(30 X 8 - 15)</b>	STANDARD	94007349		12	6.0	5.50 BD ; 5.5	8.1	30.5	TT	
<b>7.50 - 15</b>	STANDARD	94007370		12	6.0	6.00 S ; 6.5	8.7	30.9	TT	
<b>7.50 - 15</b> <b>(7.50 - 15 ( 32" OD ))</b>	STANDARD	94007325		14	6.0	6.00 S ; 6.5	8.7	32	TT	
<b>7.50 - 15</b>	STANDARD	94007387		14	6.0	6.00 S ; 6.5	8.7	30.9	TT	
<b>8.15 - 15</b> <b>(28 X 9 - 15)</b>	STANDARD	94007257		12	7.0	7.00 BD	8.5	28.3	TT	
<b>8.15 - 15</b> <b>(28 X 9 - 15)</b>	STANDARD	94007271		14	7.0	7.00 BD	8.5	28.3	TT	E11-106R-003631
<b>8.25 - 15</b>	STANDARD	94007295		12	6.5	6.0 ; 7.0	9.3	33.6	TT	
<b>8.25 - 15</b>	STANDARD	94007301		14	6.5	6.0 ; 7.0	9.3	33.6	TT	E11-106R-003402

Printed on 25/04/2024 23:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..