

PORTMAX PM 93 PLUS - Technical Specifications



Description

PORTMAX PM 93 PLUS has been specially designed for straddle carriers in port container handling operations. It is an All Steel radial tire with multilayer steel belts providing a greater stability and durability. Its special antistatic tread compound ensures a particular heat resistance and a longer tire life. PORTMAX PM 93 PLUS offers reduced rolling resistance improving fuel economy.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Straddle carrier

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 R 25
LI/SS	200 A5

Dimensions US Standard

Usa code	94047680
Overall Width (inch)	16.7
Overall Diameter (inch)	59.6
Static Loaded Radius (inch)	27.5
Rolling Circumference (inch)	180.4
Rim Rec	11.25/2.0
Star Rating	**

Load capacity (lbs)

mph / psi	145
15	30900

Printed on 17/04/2024 04:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..