

PUDDLE SPECIAL (B) - Technical Specifications



Description

PUDDLE SPECIAL is a R-2 agricultural tire specifically designed for operations in paddy fields. The extra deep tread design along with the special lug pattern provides best grip and excellent traction even on wet and soft soil. The wide center bar provides better adaptability for road applications and provides extraordinary service performance. In addition, PUDDLE SPECIAL shows superior self-cleaning features and excellent durability.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TT
Tyre Size	120/90 - 26
LI/SS	90 A2

Dimensions US Standard

Usa code	94059515
Ply Rating	6
Section Width (inch)	5
Overall Diameter (inch)	37
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	112.1
Rim Rec	4 JA
ECE	E11-106R-005236

Load capacity (lbs)

mph / psi	44
5	1320

Printed on 24/04/2024 17:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..