RIB 774 (A) - Technical Specifications

Description

RIB 774 (A) is a low-section implement tire offering high load capacity and a long tire life-cycle. It is suitable for hay harvesting and transport applications with balers and trailers.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Baler • Hay Harvester • Trailer

Version	STANDARD
Type	TL
Tyre Size	250/65 - 14.5
LI/SS FREE ROLLING	119 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	255
Overall Diameter (mm)	690
Static Loaded Radius (mm)	303
Rolling Circumference (mm)	1978
Rim Rec	AG 8.00
Rim Alt	6.75
ECE	E11-106R-003532

Load capacity (Kg)

km/h / bar	4.70
10 FR	1905
25 FR	1620
30 FR	1525
40 FR	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 08:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..