



RIB 774 (C) - Data Sheet

Description

RIB 774 (C) is a low-section and narrow-width implement tire. It is ideal for hay harvesting and transport applications with balers and trailers, both on- and off-the-road. It features great load capacity and a long tire life-cycle.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Baler • Hay Harvester • Trailer



| SIZE | Version | USACode | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|----------|----------|--------------------|----|---------|---------|------|------|------|------|------|-----------------|
| 19.0/45 - 17 | STANDARD | 94027330 | 138 A8 | 10 | 16.00 | | 17.9 | 33.3 | 15.2 | 99.1 | TL | E11-106R-004589 |
| 215/75 - 17.5 | STANDARD | 94038084 | 139 A8 | 16 | 6.75 | | 8.7 | 30.5 | 14.2 | 90.9 | TL | E4-54R-0015341 |
| 215/75 - 17.5 | STANDARD | 94011001 | 134 A8 | 12 | 6.75 | | 8.7 | 30.5 | 14.2 | 90.9 | TL | E11-106R-004590 |
| 225/75 - 17.5 | STANDARD | 94011025 | 134 A8 | 12 | 6.75 | | 8.7 | 30.5 | 14.2 | 90.9 | TL | E11-106R-004657 |
| 225/75 - 17.5 | STANDARD | 94011032 | 139 A8 | 16 | 6.75 | | 8.7 | 30.5 | 14.2 | 90.9 | TL | E11-106R-004591 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 06/05/2025 01:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..