

# RIDEMAX FL 693 M - Technical Specifications



## Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	560/45 R 22.5
LI/SS	152 D/149 E

## Dimensions US Standard

Usa code	94037322
Section Width (inch)	21.4
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19.3
Rolling Circumference (inch)	130.2
Rim Rec	AG 16.00
ECE	E4-106R-000629

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	2660	3010	3580	4230	4840	5380	6020	6590	7160
40	2910	3300	3910	4620	5290	5870	6580	7210	7830
30	3520	3990	4740	5600	6400	7110	7970	8730	9480
25	3950	4480	5320	6280	7200	7990	8950	9800	10650
15	4590	5200	6180	7300	8360	9280	10390	11390	12370
5	5210	5920	7040	8320	9510	10570	11840	12960	14090

Printed on 30/04/2024 01:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..