

RIDEMAX IT 696 - Technical Specifications



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	340/80 R 18 IND
LI/SS	143 A8/138 D

Dimensions US Standard

Usa code	94048960
Section Width (inch)	13.5
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	18
Rolling Circumference (inch)	117.3
Rim Rec	11 ; 11 SDC ; W 11
Rim Alt	W 10 ; 12 ; 12 SDC
ECE	E11-106R-002987

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	51	58
40	2030	2500	2970	3380	3850	4320	4630	5200
30	2190	2700	3210	3660	4160	4660	5000	5620
25	2350	2890	3430	3900	4440	4980	5350	6010
20	2810	3460	4110	4680	5330	5990	6420	7210

Printed on 25/04/2024 17:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..