

## ROCK GRIP IND4 (ECH) - Technical Specifications



### Description

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) is a bias-ply tire designed for Empty container handler in several applications including industrial handling and steelworks. The special ROCK GRIP compound ensure particular heat resistance along with great stability and durability.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Empty Container Handler

|           |                 |
|-----------|-----------------|
| Version   | PORT INDUSTRIAL |
| Type      | TL              |
| Tyre Size | 14.00 - 24      |

## Dimensions International Standard

|                            |         |
|----------------------------|---------|
| Ply Rating                 | 32      |
| Overall Width (mm)         | 375     |
| Overall Diameter (mm)      | 1410    |
| Static Loaded Radius (mm)  | 647     |
| Rolling Circumference (mm) | 4173    |
| Rim Rec                    | 10.00 W |
| TRA Code                   | IND4    |

## Load capacity (Kg)

|            |       |
|------------|-------|
| km/h / bar | 10.00 |
| 10         | 14175 |

Printed on 29/04/2024 14:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..