



ROCK GRIP L4 - Data Sheet



Description

ROCK GRIP (L-4) is a bias-ply tire designed for wheel loader operations in severe loading service and on rough ground conditions. Its specially designed, cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The (L-4) tread depth provides an extended tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Dozer • Loader

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	94031214	L4	24	10.00/1.5		14.8	55.5	25.6	164.3	TT
14.00 - 25	STANDARD	94031146	L4	24	10.00/1.5		14.8	55.5	25.6	164.3	TL
14.00 - 25	STANDARD	94031221	L4	28	10.00/1.5		14.8	55.5	25.6	164.3	TT
14.00 - 25	STANDARD	94031153	L4	28	10.00/1.5		14.8	55.5	25.6	164.3	TL
14.00 - 25	STANDARD	94031160	L4	32	10.00/1.5		14.8	55.5	25.6	164.3	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/05/2025 14:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..