

SKID POWER HD (A) - Technical Specifications



Description

SKID POWER HD (A) has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD (A) is the ideal tire for loose surfaces and heavy-duty service.

UM

International Standard

Construction



Machinery

Industrial: Skid Steer

Version	INDUSTRIAL
Туре	тт
Tyre Size	27 X 10 - 12 (250/75 - 12)
LI/SS	152 A2

Dimensions International Standard

Ply Rating	14
Section Width (mm)	255
Overall Diameter (mm)	700
Rim Rec	8.00 G
ECE	E11-106R-006176

Load capacity (Kg)

km/h / bar	6.90
25	2725

Printed on 04/05/2024 09:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..