



SKID POWER SK - Data Sheet



Description

SKID POWER SK has been specially designed for skid steers in construction applications. Its sidewall and rim guard protectors as well as its deep tread provide an extended tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Skid Steer

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10 - 16.5	STANDARD	94017225		10	8.25		10.6	30.5	14	90	TL	
10 - 16.5	STANDARD	94017201		8	8.25		10.6	30.5	14	90	TL	
10 - 16.5	STANDARD	94047109	138 A2	12	8.25		10.6	30.5	14	90	TL	
10 - 16.5	IMPLEMENT	94055708	116 A8	8	8.25		10.6	30.5	14	90	TL	E11-106R-003543
10 - 16.5	IMPLEMENT	94055715	120 A8	10	8.25		10.6	30.5	14	90	TL	E11-106R-003544
12 - 16.5	IMPLEMENT	94055746	130 A8	12	9.75		12.3	32.5	14.8	95.8	TL	E11-106R-003568
12 - 16.5	IMPLEMENT	94055722	125 A8	10	9.75		12.3	32.5	14.8	95.8	TL	E11-106R-003545
12 - 16.5	STANDARD	94017249		10	9.75		12.3	32.5	14.8	95.8	TL	
12 - 16.5	STANDARD	94017263		12	9.75		12.3	32.5	14.8	95.8	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 03/05/2025 05:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..