

SKID MAX SR-SKIDDER - Technical Specifications



Description

SKID MAX SR-SKIDDER is the new BKT All Steel radial tire specially developed for use in very heavy work environments on hard improved surfaces like road maintenance and waste dump with skid steers, backhoe loaders and telehandlers. Thanks to the strong steel casing and belt construction, this tire provides superior durability and high load carrying capacity.

The robust and wide tread pattern designed with continuous center rib, together with an extremely abrasion resistant and antistatic tread compound, ensures excellent traction and long wear life. The extra thick sidewall and the tough casing provide also exceptional durability minimizing the risk of punctures and accidental damages thereby reducing machine downtime.

The specially designed rim guard guarantees protection against flats and wheel damage in the rim flange area. Do not forget that SKID MAX SR-SKIDDER provides also excellent comfort and stability during your daily work.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Loader • Skid Steer • Telehandler

Version	INDUSTRIAL
Type	TL
Tyre Size	300/70 R 16.5 (12 R 16.5)
LI/SS	137 A8/B

Dimensions US Standard

Usa code	94069439
Overall Width (inch)	12
Overall Diameter (inch)	32.7
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	99.6
Rim Rec	9.75
ECE	E11-106R-007162

Load capacity (lbs)

mph / psi	73
25	5070
30	5070

Printed on 29/04/2024 19:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..