

## SM 55 L5S - Technical Specifications



### Description

SM 55 (L-5S) is a bias-ply tire ideal for underground mining operations. The specially designed cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The extra-deep L-5 S tread depth guarantees an extended tire life. The tire is also available in a steel-belted version.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Low Profile Dump Truck (LPDT) • Underground Mining Vehicle

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

## Dimensions US Standard

Usa code	94030835
Ply Rating	24
Overall Width (inch)	12.2
Overall Diameter (inch)	50.2
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	148.7
Rim Rec	8.5
Rim Alt	7.33 V ; 8 ; 8.00 V ; 8.50 V
TRA Code	L5S

## Load capacity (lbs)

	mph / psi	141
	5	16750
	10	14570
	15	13400

Printed on 03/05/2024 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..