



## SNOW - RIDE (B) - Data Sheet

### Description

SNOW-RIDE is particularly suitable for road applications in winter conditions with skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Dozer • Loader



SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH
16.9 - 24	STANDARD		12	DW 15 L	DW 14 L	429	1310	590	3930	625	TL	1
18.4 - 24	STANDARD		12	DW 16 L	DW 15 L	475	1375	625	4089	650	TL	1
15.5 - 25	STANDARD	L2	12	12.00/1.3		395	1280	569	3818		TL	0
17.5 - 25	STANDARD	L2	16	14.00/1.5		445	1348	608	4044		TL	0
17.5 - 25	STANDARD	L2	12	14.00/1.5		445	1348	608	4044		TL	0
20.5 - 25	STANDARD	L2	16	17.00/2.0	17.00/1.7	537	1492	652	4423		TL	
23.5 - 25	STANDARD	L2	16	19.50/2.5		612	1630	693	4800		TL	

Printed on 17/04/2024 17:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..