

SR 234 - Technical Specifications



Description

SR 234 is a versatile All-Steel radial tire for agricultural implements that can be fitted on harvesters and balers, tillage toolbars, seeders, large feed mixers, and anhydrous ammonia trailers. Designed with VF (Very High Flexion) technology, SR 234 can carry up to 40% more load than a standard tire of the same size at the same inflation pressure. Thanks to its wide footprint and ability to operate at lower pressure, this VF tire ensures reduced soil compaction preserving soil fertility and porosity in addition to enhanced traction. The strong steel-belted casing and a multi-rib tread pattern along with a specially engineered compound provide uniform tread wear and great durability. The low rolling resistance enhances fuel efficiency on the road and a smooth ride. The hexagonal bead has been designed for easy mounting and a secure rim fitment. SR 234 is the ideal tire for operators looking for great performance both in the fields and on the road.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Baler • Harvester • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	VF 445/50 R 22.5
LI/SS	167 D

Dimensions US Standard

Usa code	94512799
Overall Width (inch)	17.2
Overall Diameter (inch)	40.1
Static Loaded Radius (inch)	17.8
Rolling Circumference (inch)	120.1
Rim Rec	14.00
ECE	E11-106R-0010963
TRA Code	I2

Load capacity (lbs)

mph/psi	98
40	12000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/05/2025 23:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..