



SR 713 - Data Sheet



Description

SR 713 is an All Steel radial tire with VF technology for farming implements. The tire features a strong multi-ply steel-belted casing and a multi-rib tread pattern ensuring low rolling resistance and a uniform tread wear. Thanks to its large footprint, this VF tire provides reduced soil compaction. SR 713 excels in both performance and reliability offering excellent speed levels even on the road.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Implement Machinery

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
VF 245/70 R 19.5	STANDARD	I1	142 D	7.50		245	844	373	2559	TL	E11-106R-006978
VF 265/70 R 19.5	STANDARD	I1	146 D	7.50	8.25	255	873	391	2612	TL	E11-106R-007581
VF 255/70 R 22.5	STANDARD	I1	149 D	8.25	7.50	255	933	406	2790	TL	E11-106R-006860
VF 295/75 R 22.5	STANDARD	I1	151 D	9.00	8.25	280	1020	449	3044	TL	E11-106R-005500
VF 295/75 R 22.5	STANDARD	I1	155 D	9.00	8.25	280	1020	449	3044	TL	E11-106R-006977
VF 385/65 R 22.5	STANDARD	I1	163 D	11.75	12.25	385	1080	487	3251	TL	E11-106R-007881
VF 445/65 R 22.5	STANDARD	I1	169 D	13.00	14.00	440	1160	533	3515	TL	E11-106R-005501
VF 445/65 R 22.5	STANDARD	I1	176 D	13.00	14.00	440	1160	533	3515	TL	E11-106R-006976

Printed on 27/04/2024 09:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..