



## STEER FARM - Data Sheet

### Description

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: 2WD Tractor



SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
5.20 - 14	STANDARD	F2	75 A6	6	3.50 D	4.00 E	135	625	296	1837	TT	E11-106R-004092
6.00 - 16	STANDARD	F2	94 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F	170	740	353	2279	TT	E4-106R-002186
6.50 - 16	STANDARD	F2	98 A6	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	185	770	0	0	TT	E4-106R-002187
7.50 - 16	STANDARD	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	205	805	378	2451	TT	E11-106R-003547
7.50 - 16	STANDARD	F2	109 A6	10	5.50 F	5.00 F ; 5 K ; 6.00 F	205	805	378	2451	TT	
6.50 - 20	STANDARD	F2	101 A6	8	5.50 F	4.00 E ; 5.00 F	196	878	418	2701	TT	E4-106R-002833

Printed on 03/12/2023 14:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..