

## SUPER TRAX HD - Technical Specifications



### Description

SUPER TRAX HD has been specifically engineered for forklifts in heavy-duty material handling operations, including port and mining applications. The extra deep tread is made of a unique wear-resistant tread compound ensuring a longer service life. SUPER TRAX HD features a strong casing and a reinforced sidewall resulting in both excellent stability and maneuvering in lift mode. The specially designed rim guard provides protection against flats and wheel damage in the rim flange area.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	8.25 - 15

## Dimensions US Standard

Usa code	94056569
Ply Rating	16
Section Width (inch)	9.6
Overall Diameter (inch)	33.3
Static Loaded Radius (inch)	15.6
Rolling Circumference (inch)	95.8
Rim Rec	6.50
Rim Alt	7.0

## Load capacity (lbs)

mph / psi	134
15 LOAD WHEEL	10175
15 STEER WHEEL	7825
5 OTHER VEHICLES	10175
15 OTHER VEHICLES	7825
STATIC SIDE LOADER	11815

Printed on 19/04/2024 17:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..