



SUPER TRAX HD - Data Sheet



Description

SUPER TRAX HD has been specifically engineered for forklifts in heavy-duty material handling operations, including port and mining applications. The extra deep tread is made of a unique wear-resistant tread compound ensuring a longer service life. SUPER TRAX HD features a strong casing and a reinforced sidewall resulting in both excellent stability and maneuvering in lift mode. The specially designed rim guard provides protection against flats and wheel damage in the rim flange area.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Forklift

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
6.00 - 9	STANDARD	94055449	12	4.00 E		6.6	21.6	10.1	65.8	TT
6.50 - 10	STANDARD	94052936	12	5.00 F	5.50 F	7.7	23.6	11.1	72.4	TT
7.00 - 12	STANDARD	94053759	14	5.00 S		7.9	27.2	12.7	82.2	TT
8.15 - 15 (28 X 9 - 15)	STANDARD	94056552	14	7.00	7 BD	8.7	28.1	13.1	85.4	TT
8.25 - 15	STANDARD	94056569	16	6.50	7.0	9.6	33.3	15.6	95.8	TT

Printed on 02/05/2024 09:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..