

# **TF 9090 - Technical Specifications**



## **Description**

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

#### **UM**

**US Standard** 

#### Construction



## Machinery

Agriculture: Small Tractor

Industrial: Trailer

Version	STANDARD
Туре	π
Tyre Size	10.00 - 16
LI/SS	111 A8

### **Dimensions US Standard**

Usa code	94032501
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	16.1
Rolling Circumference (inch)	106.9
Rim Rec	W 8
Rim Alt	W 8 L
ECE	E4-106R-002671
TRA Code	F2

## Load capacity (lbs)

mph / psi	86
25	2400

#### Printed on 04/05/2024 21:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..