

# **TF 9090 - Technical Specifications**



## **Description**

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

#### **UM**

International Standard

### Construction



## Machinery

Agriculture: Small Tractor

Industrial: Trailer

Version	SPECIAL
Туре	ΤΤ
Tyre Size	7.50 - 18
LI/SS	106 A6

## **Dimensions International Standard**

Ply Rating	8
Section Width (mm)	207
Overall Diameter (mm)	860
Static Loaded Radius (mm)	404
Rolling Circumference (mm)	2562
Rim Rec	5.50 F
ECE	E11-106R-004318
TRA Code	F2

## Load capacity (Kg)

km/h / bar	3.70
30	950

#### Printed on 04/05/2024 19:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..