

## TF 9090 - Technical Specifications



### Description

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Small Tractor  
Industrial: Trailer

Version	STANDARD
Type	TT
Tyre Size	7.50 - 20
LI/SS	109 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	205
Overall Diameter (mm)	915
Static Loaded Radius (mm)	431
Rolling Circumference (mm)	2725
Rim Rec	5.50 F
Rim Alt	5.00 F
ECE	E4-106R-002710
TRA Code	F2

## Load capacity (Kg)

km/h / bar	3.40
30	1030

Printed on 25/04/2024 18:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..